

Mainstreet & Village MT Building Specifications

ALL HOMES ARE BUILT GREEN READY AND ENERGY STAR READY

STRUCTURAL

- Exterior Walls: 2"x 4" wall studs, 16" o.c.
- Interior Walls: 2"x 4" wall studs, 24" o.c.
- Single top plates on interior walls
- Mating Walls: 2"x 3" and/or 2"x4" wall studs, 16" o.c.
- Floor Joist: 2"x 10", 19.2" o.c. (2"x 8", 16" o.c. for 24' wide models)
- Subfloor System: ¾" tongue-and-groove OSB
- Exterior & Gable End Wall Sheathing: 7/16" OSB
- Roof Pitch: Ranch & 2-Story 7/12 storage truss 24" o.c., Cape 12/12 truss 24" o.c.
- Roof Sheathing: 7/16" OSB with ply-clips
- Overhangs: 11" fixed
- Ceiling Height: 8'
- Gable Extensions: 12" with drip edge

PLUMBING

- Bath Fixtures: White
- Tubs and Showers: Fiberglass/white
- Master bath Showers to have glass doors
- Toilets: Elongated, vitreous china
- Plumbing Supply System: Pex
- Drain, Waste & Vent System: PVC
- Water Heater: Electric 50 gallon high efficiency
- Kitchen Sink: Deep stainless steel, double bowl
- Kitchen Faucet: Single lever with Sprayer
- Bath Faucets: Dual handle with chrome Finish
- Whole house shut off valve located in washer box, supplied and site installed for basement plans

INSULATION & HEATING/COOLING PREPARATION

- Floor: R-19 insulation
- Exterior Walls: R-13 insulation
- Ceiling: R30 insulation
- Toe Kick Registers @ kitchen & baths

APPLIANCES

- Standard Dishwasher
- Standard Clean Electric Range
- Range Hood: Vented with light & fan
- All Others Optional

EXTERIOR

- Siding: Vinyl lap with white corner posts
- Vinyl fascia
- Roof Shingles: 20 year three tab fiberglass over 30 lb asphalt felt
- Ridge ventilation system
- Windows: Kinro single-hung insulated vinyl, DP50 Low-E with 6/6 grills and screens,
- Exterior window treatment at front elevation (as shown on floor plan)
- Exterior Door: as shown on floor plan with deluxe hardware on front and deadbolts on front & back
- House Wrap

INTERIOR FINISH

- Walls: ½" drywall primed with smooth finish, bone white
- Ceilings: 1/2" high strength ceiling drywall, taped and stippled, painted bone white
- Base Molding: 3 ¼" speed/finished coat
- Door & Window Casing: 2 ¼" colonial/primed & finished
- Stairs: Sloped wall
- Carpet: 25oz FHA with deluxe padding (shipped loose)
- Kitchen/Bath/Utility/Foyer Flooring: NAFCO premium vinyl floor tiles
- Interior Doors: Six panel hardboard with lever locksets
- Cabinets: Sundale flat panel square 30'/36" wall with crown, no furr down
- Counter Tops: Square edge with 1 row ceramic backsplash
- Lavinette Mirrors: Pencil edge
- Shower rods and bath accessories by purchaser
- Closet Shelving: in all closets and over washer/dryer

ELECTRICAL

- Main Electric Panel: 200AMP
- Smoke Detectors: Per plan
- Interior Lighting: Wire & brace in living room & bedrooms with 2 switches and light fixtures
- Recessed Lights: In kitchen, foyer & over shower
- Wall mounted vanity lighting
- Phone Jacks: 1 outlet in living room
- Return Air Grille with plenum and pull wire for thermostat
- Electric Box: At exterior walls, infiltration sealed
- Front & Rear exterior receptacles
- Exhaust Fans: Vented to exterior
- Wiring: Nonmetallic, 12 gauge min

Due to changing technology and the continuing possibility of shortages, Nationwide Custom Homes reserves the right to substitute products and procedures of equal or better quality at any time. These substitutions may be made without notice, but will always be in the best interest of our customers.